



T&T BISSO, LLC

USA +1 713-534-0700 • Singapore +65 6591 5288
www.ttbisso.com • info@ttbisso.com

TT-1400 FIRE PUMP

Capacity	6,000 GPM @ 170 psi
Monitors	3 x 4"
Hose Connections	2 x 5"
	8 x 2.5"
Weight	17,000 pounds
Throw Distance	300 feet



TT-750 FIRE PUMP

Capacity	3,300 GPM @ 190 psi
Monitors	1 x ALCO HR 377
Booster Pump	3,300 GPM @ 30' head
Hose Connections	5 x 2.5"
	3 x 1.5"
Foam Induction	0-6%
Weight	5,400 pounds
Throw Distance	450 feet



TT-600 FIRE PUMP

Capacity	2,650 GPM @ 190 psi
Monitors	2 x ALCO HR 376
Hose Connections	5 x 2.5"
	3 x 1.5"
Foam Proportioner	Around the pump 0-6%
Weight	6,600 pounds
Throw Distance	300 feet

Placing two units on a vessel meets the pumping requirements for a Class A fire boat.



TT-450 FIRE PUMP

Capacity	2,000 GPM @ 200 psi
Monitors	1 x 4"
Hose Connections	3 x 2.5"
Foam Induction	In-Line
Weight	2,500 pounds
Throw Distance	300 feet

