



T&T BISSO, LLC

USA +1 713-534-0700 • Singapore +65 6591 5288
www.ttbisso.com • info@ttbisso.com

FIRE PUMPS

TT-1400

| | |
|------------------|---------------------|
| Capacity | 6,000 GPM @ 170 psi |
| Monitors | 3 x 4" |
| Hose Connections | 2 x 5", 8 x 2.5" |
| Weight | 17,000 lbs |
| Throw Distance | 300 feet |



TT-750

| | |
|------------------|----------------------|
| Capacity | 3,300 GPM @ 190 psi |
| Monitors | 1 x ALCO HR 377 |
| Booster Pump | 3,300 GPM @ 30' head |
| Hose Connections | 5 x 2.5", 3 x 1.5" |
| Foam Induction | 0-6% |
| Weight | 5,400 lbs |
| Throw Distance | 450 feet |



TT-600

| | |
|-------------------|----------------------|
| Capacity | 2,650 GPM @ 190 psi |
| Monitors | 2 x ALCO HR 376 |
| Hose Connections | 5 x 2.5", 3 x 1.5" |
| Foam Proportioner | Around the pump 0-6% |
| Weight | 6,600 lbs |
| Throw Distance | 300 feet |



Placing two units on a vessel meets the pumping requirements for a Class A fire boat.

TT-450

| | |
|------------------|---------------------|
| Capacity | 2,000 GPM @ 200 psi |
| Monitors | 1 x 4" |
| Hose Connections | 3 x 2.5" |
| Foam Induction | In-Line |
| Weight | 2,500 lbs |
| Throw Distance | 300 feet |

